

SCHÜMANN / STEIER, INC.

2525 Ponce de Leon Blvd., Suite 650 • Coral Gables, Florida 33134 • Tel: (305) 442-2999 Fax: (305) 442-9666

PRODUCT BULLETIN

IDEAL[®] OIL 32

<i>Property</i>	<i>Method</i>	<i>Specifications</i>	<i>Typical Value</i>
Viscosity at 40°C, cSt	D445	29.4 – 34.6	32
Viscosity at 100°C, cSt	D445	---	5.3
Viscosity Index	D2270	92 min	100
API Gravity, °	D4052 (calc)	31.5 – 34.5	32.6
Color, ASTM	D1500	0.5 max	L0.5
Flash Point, °F	D92	---	380
Pour Point, °F	D97	---	+15
Water Separation at 130°F, emulsion vol, ml	D1401	40–37–3(30) max	40–40–0
Water Separation Time at 130°F, minutes	D1401	---	15
Oxidation Stability, hrs	D943	---	8000+

IDEAL[®] 32 is a superior quality turbine lubricant formulated with a white mineral oil base and an additive system designed for long service life. It is highly resistant to harmful sludge and varnish formation and fully inhibited against harmful oxidation, rust and corrosion.

SCHUMANN/STEIER, INC EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY OR FITNESS, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF IDEAL[®] 32 FOR USE IN ANY SECONDARY PRODUCTS INCLUDING THE ACTUAL RESULTS OF ITS USE IN ANY SUCH PRODUCTS. SCHUMANN/STEIER, INC ALSO EXPRESSLY DISCLAIMS THE ABOVE WARRANTIES RESULTING FROM THE USE OF THIS PRODUCT OR ANY SAMPLE OF THIS PRODUCT IN ANY SECONDARY PRODUCTS.